

Electrode Holders

ME Series Holders



Previous



Next

Table of Contents

Product Index

Search

Home

Contact Us



Previous



Next

Applications

- Intracellular and Extracellular Recording
- Microiontophoresis

Pressure Ports

- A – Accepts 1.5 mm (1/16") tubing
- B – Accepts 2.4 mm (3/32") tubing
- ML – Accepts female Luer fitting
- FL – Accepts male Luer fitting
- T* – Accepts 1/4-28 male thread fitting

Specifications

Body Material	9.3 mm diameter acrylic
Body Style	Straight
Connector	2 mm jack
Coupling	Ag/AgCl pellet or Ag Wire
Standard Glass Sizes	1.0, 1.2, 1.5 and 2.0 mm
Handle	6.3 mm diameter x 6.3 cm long, threaded to attach to holder.



MEW-FxxT



MEW-FxxFL

* Holders with the T port are compatible with the Picospritzer® system made by General Valve Corp.

PE SERIES Holders

Catalog No.	\$	Wire/Pellet	Body Style	Port	Connector	Glass OD (mm)	Model	
BS4 64-1220		Straight	2 mm Jack	Wire	1/16" barb	1.0	MEW-F10A	
BS4 64-1221						1.2	MEW-F12A	
BS4 64-1222						1.5	MEW-F15A	
BS4 64-1223						2.0	MEW-F20A	
BS4 64-1224					1/32" barb	1.0	MEW-F10B	
BS4 64-1225						1.2	MEW-F12B	
BS4 64-1226						1.5	MEW-F15B	
BS4 64-1227						2.0	MEW-F20B	
BS4 64-1232					male Luer	1.0	MEW-F10ML	
BS4 64-1233						1.2	MEW-F12ML	
BS4 64-1234						1.5	MEW-F15ML	
BS4 64-1235						2.0	MEW-F20ML	
BS4 64-1228					female Luer	1.0	MEW-F10FL	
BS4 64-1229						1.2	MEW-F12FL	
BS4 64-1230						1.5	MEW-F15FL	
BS4 64-1231						2.0	MEW-F20FL	
BS4 64-1236					threaded	1.0	MEW-F10T	
BS4 64-1237					1/4-28	1.2	MEW-F12T	
BS4 64-1238						1.5	MEW-F15T	
BS4 64-1239						2.0	MEW-F20T	
BS4 64-1180		Straight	2 mm Jack	Pellet	1/16" barb	1.0	MEP-F10A	
BS4 64-1181						1.2	MEP-F12A	
BS4 64-1182						1.5	MEP-F15A	
BS4 64-1183						2.0	MEP-F20A	
BS4 64-1184					1/32" barb	1.0	MEP-F10B	
BS4 64-1185						1.2	MEP-F12B	
BS4 64-1186						1.5	MEP-F15B	
BS4 64-1187						2.0	MEP-F20B	
BS4 64-1192					male Luer	1.0	MEP-F10ML	
BS4 64-1193						1.2	MEP-F12ML	
BS4 64-1194						1.5	MEP-F15ML	
BS4 64-1195						2.0	MEP-F20ML	